



Z Rail For Connectors DIN 41 612 (F)



With 84 x M2.5 thread.  
 Material:  
 Extruded aluminum  
 Surface Finish:  
 Clear chromated



Usable width (HP)	Packs of	Order No.
4	1	3684597
8	1	3684598
20	1	3684599
40	1	3684965
42	1	3684600
63	1	3684601
84	1	3684602
84	2	3685271

Note: Order assembly screws separately.

M2.5 x 6	Pac ks of	Order No.
	100	3654340

Threaded Insert (I)



With M 2.5 threaded holes in a 1HP pitch pattern. For pushing into front horizontal rails and rear rails of Ripac ECO, type A and type B.  
 Material:  
 Steel  
 Surface Finish:  
 Zinc-plated, passivated

Usable width (HP)	Packs of	Order No.
4	1	3684603
8	1	3684604
12	1	3684605
16	1	3684606
20	1	3684607
21	1	3686149
40	1	3684966
42	1	3684608
63	1	3684609
84	1	3684610

EMC Gaskets, Horizontal (K)



As horizontal EMC protection. For snapping onto the front horizontal rails.  
 Material:  
 Stainless steel



Usable width (HP)	Packs of	Order No.
For upper / lower horizontal rail		
40	1	3684974
84	1	3684808
84	10	3684246
When dividing 6U into 2 x 3U, between two horizontal rails		
84	1	3685789
84	10	3685229

Identification Strips (J)



For identifying the installation positions on the subrack, self-adhesive. The following versions are available:  
 ■ 4 mm wide: For front rails, horizontal rails  
 ■ 4 mm wide: For rear horizontal rails  
 ■ 2 mm wide: For front horizontal rails (groove)

Width	Packs of	Labeling	Order No.
4 mm	2	1 ... 84	3687575*
4 mm	2	1 ... 168	3687577
4 mm	2	84 ... 1	3687574*
2 mm	2	1 ... 84	3687576*

\* Extended delivery times